

PolarTech, PT PRO

POLARTECH



Technical data:

<i>Dimension L x W x H:</i>	710 x 520 x 970 mm
<i>Weight:</i>	53 kg
<i>Air flow range:</i>	1 -5 m ³ /min.
<i>Blast pressure range:</i>	2 – 10 bar
<i>Liquid CO₂ consumption:</i>	0,25 – 1,5 kg/pr. min. (variable feed).
<i>Liquid CO₂ operating press:</i>	20 – 70 bar
<i>Power supply:</i>	110V – 230V / AC 50 – 60 Hz
<i>Air quality:</i>	Dry and free of oil and particles.
<i>Noise:</i>	60 – 120 dB (A) depending on nozzle and pressure.

Standard equipment:

- Adjustment of air pressure.
- Adjustable feed of CO₂.
- Safety switch.

<i>Blasting hose:</i>	5 m w. quick coupling. CO ₂ hose. Electrical connection. Protective sleeve.
<i>Air supply hose:</i>	10 m ¾" w. claw coupling.
<i>Electrical cord:</i>	10 m
<i>Co₂ supply hose:</i>	1,5 m 3/8" incl. coupling.
<i>Standard round nozzle (customer choice).</i>	

Optional:

- Range of round, flat and bended nozzles.
- Blasting hose, complete, various length.
- Air supply hose, various length.
- LED lamp.

